

HPS 41 SERIES

Processed Active Speaker 15 "

SPECIFICATIONS	
Frequency response	35-18KHZ
Coverage	H90° × V60°
Continuous	400W
Music	800w
Peak	1600w
Sensitivity 1w/1m	94dB
Peak spl	112dB
System impedance	4OHM
Crossover section	2 way
Cross over frequency	5000HZ
Input Connector	6.35TRS,XLR
Dimension (hxwxd)	50.5×40.5×77.5cm

The unit speaker is not only the flagship of the line,

it is also the reference standard for the entire class.



Model	HPS4108/A	HPS4110/A	HPS4112/A	HPS4115/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofer	8 " woofer,30oz,38mm vc,4ohm/8ohm	10" woofer,40oz,50mm vc,4ohm/8ohm	12 " woofer,50oz,65mm vc,4ohm/8ohm	15 " woofer,60oz,75mm vc,4ohm/8ohm
Tweeter	25mm Ti.Diap.driver,10OZ,8ohm	25mm Ti.Diap.driver,10OZ,8ohm	34mm Ti.Diap.driver,14OZ,8ohm	44mm Ti.Diap.driver,23OZ,8ohm