# PLASTIC CABINET SPEAKER



## HPS 42 SERIES

Processed Active Speaker 15 "

| SPECIFICATIONS | |
|---|---|
| Frequency response | 35-20KHZ |
| Coverage | H90° × V30° |
| Continuous | 400W |
| Music | 800w |
| Peak | 1600w |
| Sensitivity 1w/1m | 98db |
| Peak spl | 130dB |
| System impedance | 4 OHM |
| Crossover section | 2 way |
| Cross over frequency | 1200HZ/3600HZ |
| Input Connector | RCA,6.35TRS,XLR AUX |
| Dimension (hxwxd) | 50×43×75.7cm |

with amazing feture and the ultra compact power amplifier, based on the successful digital amplifier technology for maximum efficiency.



| Model | HPS4208/A | HPS4210/A | HPS4212/A | HPS4215/A |
|---|---|---|---|---|
| System type | 2-way Model speaker box | 2-way Model speaker box | 2-way Model speaker box | 2-way Model speaker box |
| Woofer | 8 " woofer,30oz,38mm vc,4ohm/8ohm | 10 " woofer,40oz,50mm vc,4ohm/8ohm | 12 " woofer,50oz,65mm vc,4ohm/8ohm | 15 " woofer,60oz,75mm vc,4ohm/8ohm |
| Tweeter | 25mm Ti.Diap.driver,10OZ,8ohm | 25mm Ti.Diap.driver,10OZ,8ohm | 34mm Ti.Diap.driver,14OZ,8ohm | 44mm Ti.Diap.driver,23OZ,8ohm |