

HPS 48 SERIES

Processed Active Speaker 15 "

SPECIFICATIONS	
Frequency response	45-18KHZ
Coverage	H100° × V60°
Continuous	75W
Music	150W
Peak	300W
Sensitivity 1w/1m	95dB
Peak spl	120dB
System impedance	4 OHM
Crossover section	2 way
Cross over frequency	3500HZ
Input Connector	XLR,RCA,6.35TRS
Dimension (hxwxd)	52×48×75.5cm

The speaker offers powered loudspeaker with modern AB Analog Amplifier technology, without having to miss out on professional feature and outstanding audio performance.



Model	HPS4808/A	HPS4810/A	HPS4812/A	HPS4815/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofer	8 " woofer,30oz,38mm vc,4ohm/8ohm	10 " woofer,40oz,50mm vc,4ohm/8ohm	12 " woofer,50oz,65mm vc,4ohm/8ohm	15 " woofer,60oz,75mm vc,4ohm/8ohm
Tweeter	25mm Ti.Diap.driver,10OZ,8ohm	25mm Ti.Diap.driver,10OZ,8ohm	34mm Ti.Diap.driver,14OZ,8ohm	44mm Ti.Diap.driver,23OZ,8ohm