

HPS 54 SERIES

Processed Active Speaker 15 "

SPECIFICATIONS	
Frequency response	45~18KHZ
Coverage	H100° × V60°
Continuous	350W
Music	700W
Peak	1400W
Sensitivity 1w/1m	96dB
Peak spl	125dB
System impedance	4 OHM
Crossover section	2 way
Cross over frequency	1.3KHZ，3.6KHZ
Input Connector	6.35TRS,RCA,XLR
Dimension (hxwxd)	50.5×45.0×74.5cm

The unit speaker is not only the line,it is also the reference standard for the entire entire class.



Model	HPS5408/A	HPS5410/A	HPS5412/A	HPS5415/A
System type	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box	2-way Model speaker box
Woofer	8 " woofer,30oz,38mm vc,4ohm/8ohm	10 " woofer,40oz,50mm vc,4ohm/8ohm	12 " woofer,50oz,65mm vc,4ohm/8ohm	15 " woofer,60oz,75mm vc,4ohm/8ohm
Tweeter	25mm Ti.Diap.driver,10OZ,8ohm	25mm Ti.Diap.driver,10OZ,8ohm	34mm Ti.Diap.driver,14OZ,8ohm	44mm Ti.Diap.driver,23OZ,8ohm